

TUNCUT M 22

Semi-synthetic cutting oil with NSF registration for the corrugated cardboard industry

Benefits

- ✓ Extended cutting life due to very good corrosion protection and outstanding lubrication effect
- ✓ Optimised strength and adhesive oil capacity to achieve a clean cutting result for longer
- ✓ Reduced lubricant consumption due to particularly good temperature and evaporation stability

Properties

- ✓ NSF H1-registered
- ✓ ISO 21469, Kosher- and Halal-certified
- ✓ Excellent strength and adhesive oil properties

Application area

- ✓ Specially developed for lubricating longitudinal cutting and groove cutting systems during the production of corrugated cardboard
- ✓ Can also be used for cleaning starch and adhesive residues and for protecting surfaces

Instructions

Observe the specifications from the machine manufacturer. TUNCUT M 22 is usually applied via automatic lubrication systems. TUNCUT M 22 can be used as a cleaning oil when applied using a cleaning cloth.

If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is used as a corrosion-protection film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCUT M 22	200 l	168.2 kg	185.2 kg	1106608	1 PCS



Technical Product Data	TUNCUT M 22
Density/conditions	0.841 g/cm ³ / in accordance with DIN 51757
Colour spectrum	Clear Transparent
Oil basis	Synthetic
Kinematic viscosity / condition	17 mm ² /s / at 40°C
Viscosity index/conditions	120 / in accordance with DIN ISO 2909
Min. flashing point /conditions	200 / in accordance with ISO 2592
Pour point	-58 °C
Min./max. temperature conditions	-40 to 200 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.