Product Information



microflex®

965 System Agent Hybrid

microflex® 965 System Agent Hybrid with the innovative ROA² technology Level 1 protects the fuel system against corrosion and deposits. In addition, it cleans the combustion chamber and injection system and reduces fuel consumption and emissions. Stabilises and protects the fuel during the typically longer service life of hybrids.





Properties

- Reliably protects the entire fuel system against corrosion
- Prevents deposits from forming in the fuel system when added regularly
- Cleans the combustion chamber and injection system
- Reduces fuel consumption when added regularly
- ✓ Improves the octane number

Benefits

- Stabilises and protects the fuel when added regularly, ideal for when fuel remains in the tank for longer periods, as is typical for hybrid vehicles
- Reduces the risk of engine damage due to LSPI (low-speed pre-ignition)
- Can reduce emissions almost to the level expected of new vehicles

Application area

- For all hybrid vehicles with petrol engines
- For cleaning the injection system on all intake-manifold and direct-injection petrol engines
- ✓ Suitable for all petrol (ethanol) mixtures

Instructions

Simply add to the fuel tank.

Dosing

Sufficient for up to 80 l of fuel (min. 10 l of fuel)

Notice

- Use regularly for optimal protection
- For hybrid vehicles, the system agent should be added every time the vehicle is refilled with fuel
- For all other petrol vehicles, the system agent should be added regularly every 5,000 km (depending on the fuel quality)

Product Description	Contents	Article Number	Packaging Unit
System Agent Hybrid	200 ml	1106757	24 PCS





PI 965 20250608