

## TUNFLUID HTC 260

Fully synthetic high-temperature oil for chain lubrication

### Benefits

- ✓ Very economical consumption due to high degree of thermal stability and extremely low boil-off
- ✓ Clean to use, as no varnish-like residues are formed even at increased operating temperatures.
- ✓ Excellent wear protection for reliable chain operation

### Properties

- ✓ Excellent creeping properties
- ✓ Ideal for medium to high speeds
- ✓ No resin or bonding effect
- ✓ Reduces friction and wear

### Application area

- ✓ Drive, control and conveyor chains in high-temperature applications, e.g. in surface treatment, drying or coating of various industrial goods
- ✓ Transport systems in automotive supply, metalworking and/or coating of household goods or packaging material manufacturing
- ✓ Conveyor chains in dryers, e.g. in the production of gypsum or mineral wool

### Instructions

Observe the machine manufacturer's specifications. Can be applied using a drip oiler, brush or automatic central lubrication system.

H2 products must not be used in areas where foodstuffs are manufactured. H2 products can be used as lubricants, release agents or corrosion inhibitors for machine parts and equipment provided that they do not come into contact with foodstuffs.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNFLUID HTC 260	200 l	181 kg	197 kg	1106828	1 PCS





Technical Product Data	TUNFLUID HTC 260
Density/conditions	0.904 g/cm <sup>3</sup> / at 20°C
Colour spectrum	Yellowish Transparent
Oil basis	Ester
Kinematic viscosity / condition	260 mm <sup>2</sup> /s / at 40°C
Min. flashing point /conditions	> 250°C / nach ISO 2592
Pour point	-27 °C
Min./max. temperature conditions	-25 to 250 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.