# Product Information

# TUNCLEAN 5110

**Multi-purpose cleaner for vehicles, buildings and machinery. Guarantees excellent cleaning of oil, grease, wax and similar dirt.**

## Properties

- ✔ Dissolves greases, oils, contaminants and dirt deposits
- ✔ In most cases, no mechanical processing is required
- ✔ Ensures quick and effective cleaning
- ✔ Readily biodegradable

## Application area

- ✔ In all areas where severe contamination occurs: Buildings and plants, machine workshops, floors and walls, interior and exterior of vehicles, tool machines and processing equipment.

## Instructions

For standard levels of contamination, the cleaner can be diluted up to 1:30; in high-pressure cleaners, it can be diluted up to 1:200. Dilution for engine wash 1:5 and for plastics 1:20. Required minimum dilution of 1:5 required for optimal effect. Touch up bare surfaces with a brush. Suitable for use in cleaning machines thanks to anti-foaming agent. Apply by hand with a sponge. Apply product with a spray bottle and wipe off with a damp sponge. Rinse with clean water. Carry out preliminary tests for material compatibility on a hidden area.

| Product Description | Contents | Weight of content | Gross weight | Article Number | Packaging Unit |
|---|---|---|---|---|---|
| TUNCLEAN 5110 | 20 l | 21.24 kg | 22.12 kg | 1107612 | 1 PCS |

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

# Product Information

| Technical Product Data | TUNCLEAN 5110 |
|---|---|
| **Density/conditions** | 1.062 g/cm³ / at 20°C |
| **Colour spectrum** | Orange |

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.