

## TUNGREASE BS

Fully synthetic special grease for long-term lubrication of friction contacts made of non-ferrous heavy metal alloys.

### Benefits

- ✓ An extremely low friction coefficient helps to save energy and promotes smooth running even under the highest pressure loads, vibrations or shock loads
- ✓ Activates the self-lubrication of all bronze materials
- ✓ Reduces running noise and vibrations as well as stick-slip behaviour
- ✓ Corrosion-resistant, resistant to ageing and shearing
- ✓ Dirt and water-repellent as well as resistant to cold and hot water
- ✓ Good compatibility with conventional sealing materials

### Properties

- ✓ With OMC2 technology for minimisation of wear. Specially adapted to the bronze/steel material pairing
- ✓ Versatile
- ✓ A high base oil viscosity and special additives ensure extremely high adhesion, so stays at the application point

### Application area

- ✓ For lubricating slide and roller bearings, spline shafts, cardan and universal joints, spindles, guides, cams, transport chains and gears
- ✓ Especially for threaded spindles, e.g. on scissor-type lifting tables

### Instructions

In accordance with technological standards for lubricating greases.

We recommend cleaning the surfaces to be lubricated beforehand with a suitable cleaner (TUNCLEAN 895 or FDB) and leaving to dry. The surfaces to be greased must be covered with a thin and even film.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNGREASE BS	0	0.4 kg	0.503 kg	1108083	12 PCS

