Product Information

TUNPRO WK with fluorescent dye

n-Hexane-free wax spray for surface protection with excellent penetration and corrosion protection properties

Benefits

- ✔ n-Hexane-free
- ✔ Reliable corrosion protection for safe storage of components, semi-finished products or finished parts
- ✔ Excellent creep properties make it easy to apply even with complex geometries
- ✔ Ideal for preserving moulds in plastic injection moulding, as the melting point means it is removed after only a few injections

Properties

- ✔ n-Hexane free
- ✔ With fluorescent dye for easy visual monitoring
- ✔ Outstanding water resistance
- ✔ Reliable corrosion protection
- ✔ Excellent creep properties

Application area

- ✔ For protecting and lubricating tools, especially for injection moulds
- ✔ For sealing and lubricating hard-to-reach areas, semi-finished products and finished parts.
- ✔ Can also be used as non-volatile punching and drawing agent in metalworking
- ✔ Corrosion protection at open sliding points, such as track guideways

Instructions

Clean parts thoroughly in advance. Shake the can well before use. Spray as evenly as possible on the parts to be protected. Check coating with a UV lamp.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNPRO WK with fluorescent dye	400 ml	0.253 kg	0.36 kg	1108357	12 PCS

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

Product Information

Technical Product Data	TUNPRO WK with fluorescent dye
Colour spectrum	Light brown

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.