

Human+Technology® 922 Dry Lubricant+

Excellent dry lubricant with a patented grease-wax matrix for maximum protection against wear and corrosion. Suitable for use at high and low temperatures. Particularly suitable for extremely dusty and dirty environments due to the very low adhesion of dirt.



Nonfood Compounds
H1



Human+Technology®

- ✓ High level of industrial safety and user protection since it is free from neurotoxic n-hexane, potentially allergenic fragrances and dyes, and harmful solvents
- ✓ No indicators of toxicological effects
- ✓ NSF H1 registered
- ✓ ISO 21469, Kosher and Halal certified
- ✓ Formula free from silicone oil, PFAS and microplastics
- ✓ Better for people and the environment due to the use of fewer potentially harmful ingredients

Properties

- ✓ Excellent, long-lasting wear reduction of the lubrication areas due to a dry protective layer with extremely good sliding properties
- ✓ Particularly low adhesion of dirt, including in very dusty and dirty environments
- ✓ High resistance at high and low temperatures for long-lasting lubrication due to boron nitride
- ✓ Very good creep effect and penetrating properties
- ✓ Particularly long-lasting corrosion protection
- ✓ Excellent sealing properties against moisture and dirt
- ✓ Prevents creaking and squeaking noises
- ✓

Application area

- ✓ For lubricating sliding surfaces, spline shafts, cardan joints, universal joints, spindles, guides, transport chains and cogs for long-lasting protection
- ✓ Particularly suitable for lubrication in very dirty, dusty and dry environments
- ✓ Provides extremely long-lasting protection against corrosion

Instructions


Refer to the product information before use. Shake the can well before use, pre-clean the areas to be lubricated and spray evenly from a distance of approx. 20 cm.

Notice

- ✓ When using the product in the food processing industry, only the minimum quantity technically required should be used.
- ✓ When using the product as a corrosion protection film, it must be completely removed before the appliance is restarted.

Product Description	Contents	Article Number	Packaging Unit
Dry Lubricant+	400 ml	1108516	12 PCS

Product Information



The information herein is the product of careful testing. It is to be considered a recommendation compliant with state of the art knowledge where use is concerned. We cannot accept any liability whatsoever in view of the multiplicity of possible uses and working methods. No contractual relationship is hence implied and no ancillary obligations arise from any contract of sale that may be made. Product information is only valid in its latest current form. TUNAP (U.K) Limited | Unit L4 Deacon Trading Estate, Morley Road, Tonbridge, Kent TN9 1RA | Telephone +44 (0) 1732 365163 | e-Mail: sales@tunap.co.uk

PI 922 20260612

[TUNAP.com](https://www.tunap.com)