

## Human+Technology®

### 904 Care and Lubricating Spray+

Silicone-free care spray for protecting and treating plastic and sealing materials. Prevents creaking noises and creates a sliding micro-film, e.g. for window guides, door seals and plastics. Can also be used as a release agent in the plastic injection moulding industry.



Nonfood Compounds  
H1



#### Human+Technology®

- ✓ High level of industrial safety and user protection since it is free from neurotoxic n-hexane, potentially allergenic fragrances and dyes, and harmful solvents
- ✓ No indicators of toxicological effects
- ✓ NSF H1 registered
- ✓ ISO 21469, Kosher and Halal certified
- ✓ Formula free from silicone oil, PFAS and microplastics
- ✓ Better for people and the environment due to the use of fewer potentially harmful ingredients

#### Properties

- ✓ Transparent lubricating, release and care oil prevents squeaking and creaking noises in plastics
- ✓ Good compatibility with conventional plastics and elastomers
- ✓ Significantly reduces friction due to grease-free sliding protection
- ✓ Formula is free from silicone
- ✓ Highly lubricating effect, e.g. in the area of window guides, seat belts, door seals and other plastics
- ✓ Wide temperature range from -25 °C to +140 °C

#### Application area

- ✓ For stiff seat belts and window guides
- ✓ For preventing unwanted noise, especially in vehicle interiors
- ✓ For the care and cleaning of rubber and plastic parts
- ✓ Mould release agent in the industrial production of plastic parts

#### Instructions

Refer to the product information before use. Shake the can well before use and spray evenly onto the surfaces to be treated from a distance of approx. 20 cm.

#### Notice

- ✓ When using the product in the food processing industry, only the minimum quantity technically required should be used. When using the product as a corrosion protection film, it must be completely removed before the appliance is restarted.

Product Description	Contents	Article Number	Packaging Unit
Care and Lubricating Spray+	400 ml	1108543	12 PCS

Technical Product Data	Care and Lubricating Spray+
<b>Colour spectrum</b>	Colourless Clear
<b>Oil basis</b>	Medical white oil
<b>Kinematic oil basis viscosity</b>	15 mm <sup>2</sup> /s
<b>Pour point</b>	-15 °C
<b>Min./max. temperature conditions</b>	-15 bis 140 °C
<b>NSF Number</b>	143413

