

TUNPRO K

Wax spray for long-term protection with good penetration and corrosion protection properties.

Benefits

- ✓ Reliable corrosion protection due to the highly adhesive, durable wax film
- ✓ The excellent temperature stability prevents dripping, even in direct sunlight
- ✓ Long-term protection with very good corrosion protection properties
- ✓ - Hybrid corrosion protection combines the benefits of corrosion protection greases and corrosion protection waxes
- ✓ - Very good performance at high and low temperatures makes it suitable for use in a wide temperature range
- ✓ - Long-lasting corrosion protection due to a highly adhesive, elastic wax film that is both touch-dry and resistant to dirt adhesion
- ✓ - Self-healing properties ensure the protective layer remains undamaged in the event of deformation or light scratches
- ✓ - Excellent creep properties during application ensure that the product forms an even film and penetrates even into hard-to-reach areas, such as small cavities and sheet metal seams
- ✓ - Reduces friction, wear and tribocorrosion while also providing excellent water resistance even in demanding applications, such as wire ropes
- ✓ exposed to challenging weather conditions

Properties

- ✓ Very good adhesion, no dripping, even in direct sunlight
- ✓ Excellent penetration and wetting ability

Application area

- ✓ For sealing and lubricating hard-to-reach areas, semi-finished products and finished parts.
- ✓ Use in industry:
- ✓ As a non-volatile punching and pulling agent
- ✓ For parts that are prone to corrosion
- ✓ Cavity conservation of parts to protect against weathering
- ✓ Corrosion protection at open sliding points, such as bed guideways
- ✓ For protecting and lubricating tools, especially for injection moulds
- ✓ Lubrication of wire parts
- ✓ Used in the automotive industry:
- ✓ Cavity sealing
- ✓ If the underbody seal is damaged
- ✓ Motor preservation
- ✓ For protection and lubrication at all sliding points exposed to weathering

Instructions

Thoroughly pre-clean parts with TUNCLEAN 895. Spray as evenly as possible on the parts to be protected. After drying, repeat the process as required to ensure the protective film is as thick as possible. Shake can well before use.

Product Information



Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNPRO K	20 l	15.6 kg	15.8 kg	1108955	1 PCS

<STEPTABLE O="PR08_1108955" OT="Product" TT="PI_2020_TechD_Industrie" VC="3834_en" VO="35404789" W="Approved" />

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20260727

TUNAP.com