

TUNSIL FB

Silicone oil-based lubricant and release agent

Benefits

- ✓ For reliable demoulding in plastic injection moulding
- ✓ Good compatibility with standard plastics, paints and elastomers makes it highly versatile
- ✓ NSF H1 registration for increased product and process reliability

Properties

- ✓ NSF H1-registered
- ✓ ISO 21469, Kosher and Halal-certified
- ✓ Transparent
- ✓ Non-contaminating and non-greasy
- ✓ High wetting capacity
- ✓ Eliminates squeaking noises

Application area

- ✓ As a lubricant for all types of machines, particularly in the plastics sector
- ✓ For lubricating all moving parts
- ✓ For protecting and conserving surfaces
- ✓ As a mould release agent, particularly in the plastics processing industry

Instructions

Spray on from a distance of approx. 20cm and wipe off with a cloth if necessary.
If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is to be used as an anti-corrosive film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNSIL FB	400 ml	0.248 kg	0.351 kg	11ACF13214A0400	12 PCS



Product Information



Technical Product Data	TUNSIL FB
Density/conditions	0.79 g/cm ³ / at 20°C
Colour spectrum	Colourless Clear
Oil basis	Silicone oil
Kinematic viscosity / condition	3.4 mm ² /s / at 40°C
Pour point	-50 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20250203

[TUNAP.com](https://www.tunap.com)