Product Information

TUNSOLID TE 812

Air-drying sliding lacquer with bright PTFE solid lubricants

Benefits

- ✔ Very good adhesion to metal surfaces for reliable wear protection of the sliding coating
- ✔ For improved operational safety with clean and dry surfaces

Properties

- ✔ High pressure absorption
- ✔ Fast-drying
- ✔ Bright and transparent
- ✔ Good compatibility with rubber, plastics and metal
- ✔ Not dust-binding
- ✔ Water-resistant

Application area

- ✔ As a single lubricant for medium-load guides and sliding surfaces where oil and grease-free lubrication is essential
- ✔ As a basic lubricant for guides and guiding ways in conjunction with suitable lubricants for preventing stick-slip.

Instructions

The surface of the material must be free of grease, clean and dry before applying the sliding lacquer. Stir or shake the container before use. Drying time: 10 minutes at 20°C.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNSOLID TE 812	400 ml	0.304 kg	0.405 kg	11ACH12284A0400	12 PCS

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

Product Information

Technical Product Data	TUNSOLID TE 812
Density/conditions	0.852 g/cm³ / at 20°C
Colour spectrum	White Cloudy

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.