

TUNPRO TR

Synthetic high-performance dry lubricant with solid lubricants

Benefits

- ✓ Excellent wax film adhesion
- ✓ For lubrication at high speeds with no dripping or shearing
- ✓ No dirt or dust adhesion due to the dry surface
- ✓ Excellent corrosion protection for a long component service life, even under adverse conditions

Properties

- ✓ Transparent
- ✓ Non-contaminating and non-greasy
- ✓ Reduces friction and wear
- ✓ NSF H2-registered
- ✓ ISO 21469, Kosher- and Halal-certified

Application area

- ✓ Suitable for lubricating all sliding surfaces, splined shafts, cardan joints, universal joints, spindles, guides, transport chains and cogs, particularly in dusty environments.

Instructions

Shake well before use. The surface should be dry and free of dust and grease. Apply a thin layer of TUNPRO TR. After approx. two minutes, spray another thin coat.

H2 products must not be used in areas where foodstuffs are manufactured. H2 products can be used as lubricants, release agents or corrosion inhibitors for machine parts and equipment provided that they do not come into contact with foodstuffs.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNPRO TR	400 ml	0.258 kg	0.46 kg	11ACH12400A0400	12 PCS



Product Information



Technical Product Data	TUNPRO TR
Density/conditions	0,707 g/cm ³ / bei 20°C
Colour spectrum	Beige
Kinematic viscosity / condition	4 mm ² /s / at 40°C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20250120

[TUNAP.com](https://www.tunap.com)