

TUNGARD FD

Synthetic H1 multi-functional oil with good wetting capacity

Benefits

- ✓ No n-Hexane - protects people and the environment
- ✓ Improved safety and user protection thanks to high flash point
- ✓ Excellent corrosion protection for a longer component service life
- ✓ NSF H1 registration for increased product and process reliability
- ✓ For lubricating and maintaining connections, chains, seals and all moving components

Properties

- ✓ NSF H1-registered
- ✓ ISO 21469, Kosher- and Halal-certified
- ✓ Colourless, transparent, non-discolouring
- ✓ Mineral oil-free formula
- ✓ Excellent creepage properties
- ✓ Good protection against oxidation and ageing
- ✓ Non-ferrous base metal corrosion protection

Application area

- ✓ For lubricating and maintaining connections, chains, seals and all moving components
- ✓ As a release agent
- ✓ As corrosion protection
- ✓ For all applications where the use of physiologically safe, mineral oil-based products, critical additives and/or critical solvents is not desired

Instructions

Pre-clean the surface to be treated. Spray on evenly from a distance of approx. 20cm.
If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is to be used as an anti-corrosive film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNGARD FD	400 ml	0.324 kg	0.327 kg	11ACH20301A0400	12 PCS



Product Information



Technical Product Data	TUNGARD FD
Density/conditions	0.805 g/cm ³ / at 20°C
Colour spectrum	Colourless Clear
Oil basis	Synthetic
Kinematic viscosity / condition	32 mm ² /s / at 40°C
Min. flashing point / conditions	61 / in accordance with ISO 2592
Pour point	-52 °C
Min./max. temperature conditions	-40 to 180 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20250203

[TUNAP.com](https://www.tunap.com)