

## TUNGARD OG

Multi-purpose lubricant spray with white solid lubricants

### Benefits

- ✓ No n-Hexane - protects people and the environment
- ✓ Contains white solid lubricants for emergency running properties and reliable lubrication during oscillating movements

### Properties

- ✓ Displaces water and moisture
- ✓ Protects against corrosion and frictional corrosion
- ✓ Clean to use
- ✓ Excellent creepage and penetration properties
- ✓ No resin or adhesive effect

### Application area

- ✓ For lubricating joints, hinges, linkages, levers, chains and guides.
- ✓ Wherever slow or oscillating motion does not allow the buildup of a hydrodynamic lubricant film.
- ✓ Excellent creepage properties make it particularly suitable for hard-to-reach lubrication points.
- ✓ In applications subject to extremely high pressures or where there is a risk of tribocorrosion due to strong vibrations.

### Instructions

Pre-clean the surface to be treated. From a distance of approx. 20cm spray an even coat. Leave to take effect briefly. Repeat if necessary.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNGARD OG	300 ml	0.26 kg	0.364 kg	11ACH20302A0300	12 PCS



Technical Product Data	TUNGARD OG
Density/conditions	0,8375 g/cm <sup>3</sup> / nach DIN 51757
Colour spectrum	Yellowish Cloudy
Oil basis	Synthetic
Flow time (4mm- Ford cup)/conditions	13 s / in accordance with DIN EN ISO 2431
Min. flashing point /conditions	61 / in accordance with ISO 2592
Pour point	-60 °C
Min./max. temperature conditions	-10 to 160 °C