

TUNCLEAN 700

NSF H1 and K1 registered cleaner for maintenance, repair and assembly.

Benefits

- ✓ Slow evaporation for maximum application time
- ✓ NSF H1 registered
- ✓ ISO 21469, Kosher- and Halal-certified
- ✓ Cleaning and temporary lubrication in physiologically and ecologically sensitive areas
- ✓ For maintenance, repair and assembly in the case of extreme grease residues

Properties

- ✓ Colourless, non-discolouring
- ✓ Good penetration
- ✓ Good compatibility with common plastics
- ✓ Removes oils, encrusted resin and silicone residues
- ✓ Evaporates without leaving any residue

Application area

- ✓ Cleaning and temporary lubrication in physiologically and ecologically sensitive areas
- ✓ For maintenance, repair and assembly in the case of extreme grease residues.

Instructions

Use a brush, cloth or similar tool to mechanically process the surfaces to be cleaned and allow to dry. If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is to be used as an anti-corrosive film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCLEAN 700	200 l	155 kg	175 kg	11ACH21700L2000	1 PCS





Technical Product Data	TUNCLEAN 700
Density/conditions	0.792 g/cm ³ / at 20°C
Colour spectrum	Colourless Clear
Evaporation number/conditions	200 / in accordance with DIN 53170
Min. flashing point /conditions	61 / in accordance with ISO 2592

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.