Product Information

TUNCLEAN Z05

Highly effective special solvent-based cleaner

Benefits

- ✔ 100 % active ingredient content due to gasification with compressed air
- ✔ Very good compatibility with glass, ceramics, metal and textiles
- ✔ Hydrocarbon alcohol-based volatile cleaner

Properties

- ✔ Fast drying time
- ✔ Very good stain removal and degreasing
- ✔ Residue-free cleaning

Application area

- ✔ For maintenance, repair and assembly in the case of extreme grease and resin deposits
- ✔ For degreasing and activating parts before gluing and painting
- ✔ Removes oils and encrusted resin, synthetic oil and silicone residues
- ✔ Ideal for residue-free cleaning

Instructions

Apply TUNCLEAN Z05 to the parts to be cleaned by spraying or dipping. Leave to soak in briefly. Perform a preliminary test to check for plastic and paint compatibility.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCLEAN Z05	400 ml	0.314 kg	0.41 kg		12 PCS

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

Product Information

Technical Product Data	TUNCLEAN Z05
Density/conditions	0.75 g/cm³ / at 20°C
Min. flashing point /conditions	-18 / in accordance with DIN 51755

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.