Product Information



TUNCLEAN Z45

Highly effective special solvent-based cleaner

Benefits

- Very good stain removal and degreasing
- ✓ 100 % active ingredient content due to gasification with compressed air
- ✔ Residue-free cleaning
- ✓ Very good compatibility with glass, ceramics, metal and textiles

Application area

- ✔ For removing stubborn dirt such as sealants, stickers or chewing gum residue
- Can be used to remove silicone before painting
- Can be used as a stain remover on textiles
- Ideal for residue-free cleaning

Instructions

Evenly spray the surfaces to be cleaned with TUNCLEAN Z45 from a distance of approx. 20 cm. If necessary, use a brush, cloth or similar tool to mechanically apply the product to the surface and allow to dry. Perform a preliminary test to check for plastic and paint compatibility.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCLEAN Z45	400 ml	0.306 kg	0.417 kg		12 PCS

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

Product Information



Technical Product Data

TUNCLEAN Z45

Colourless

Colour spectrum Refractive index/conditions

Clear 1.375 / in accordance with DIN 51423-1

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and PI 20250106 mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application. TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.