

## TUNCLEAN FDB

Physiologically safe NSF H1 cleaner for maintenance, repair and assembly.

### Benefits

- ✓ Residue-free cleaning for grease-free surfaces and easy follow-up processes
- ✓ Good compatibility with common plastics
- ✓ Evaporates without leaving any residue

### Properties

- ✓ NSF H1 registered
- ✓ ISO 21469, Kosher- and Halal-certified
- ✓ Colourless, transparent, non-discolouring
- ✓ Removes oils, encrusted resin and silicone residues
- ✓ Good creepage properties

### Application area

- ✓ Cleaning and temporary lubrication in physiologically sensitive areas
- ✓ For maintenance, repair and assembly in the case of extreme grease residues

### Instructions

Evenly spray the surfaces to be cleaned with TUNCLEAN FDB from a distance of approx. 20 cm. If necessary, use a brush, cloth or similar tool to mechanically process the surfaces and allow to dry. Perform a preliminary test to check for plastic and paint compatibility.

If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is to be used as an anti-corrosive film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCLEAN FDB	500 ml	0.378 kg	0.5 kg	11ACH21794A0500	12 PCS



Nonfood Compounds  
Program Listed H1/K1  
135-010

# Product Information



Technical Product Data	TUNCLEAN FDB
Density/conditions	0.74 g/cm <sup>3</sup> / in accordance with DIN 51757
Colour spectrum	Colourless Clear
Evaporation number/conditions	60 / in accordance with DIN 53170
Min. flashing point /conditions	36 / in accordance with ISO 2592

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20250106

[TUNAP.com](https://www.tunap.com)