Product Information

TUNFLUID DAB

Multi-purpose oil for the food processing industry

Benefits

- ✔ Versatile and powerful multi-purpose oil, ideal for reducing type variety
- ✔ Good corrosion protection for a long component life
- ✔ Good oxidation and ageing stability
- ✔ Cleans, maintains and protects at the same time
- ✔ Reduces friction and wear
- ✔ Economical to use
- ✔ Suitable as a raw material for preparation of cosmetic products

Properties

- ✔ Particularly suitable for stainless steel care
- ✔ NSF H1 registered
- ✔ ISO 21469, Kosher- and Halal-certified
- ✔ Water-white paraffin oil
- ✔

Application area

- ✔ For lubricating and protecting seals, joints, chains and any moving parts in which there is a risk of direct contact between the lubricant and foodstuffs:
- ✔ Suitable for all oil lubrication points on machines in the food industry
- ✔ Filling machines, packaging machines, sealing machines
- ✔ Chains and conveyors
- ✔ Gears
- ✔ Slide bearings, joints, pistons, guides, tube tracks
- ✔ Roller bearings
- ✔ As a release agent and lubricant
- ✔ For the care and maintenance of stainless steel in breweries, bakeries, meat factories, industrial kitchens and hospitals
- ✔ As corrosion protection throughout the food industry
- ✔ As circulating and hydraulic oil

Instructions

Application with brush, clean cleaning cloth or drip oiler.
If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is used as an anti-corrosive film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNFLUID DAB	500 ml	0.338 kg	0.47 kg	11ACI14001A0500	12 PCS

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

Product Information

Technical Product Data	TUNFLUID DAB
Density/conditions	0.862 g/cm³ / at 20°C
Colour spectrum	Colourless Clear
Oil basis	Medical white oil
Kinematic viscosity / condition	68 mm²/s / at 40°C
Min. flashing point /conditions	≥ 245 / nach ISO 2592
Pour point	-10 °C
Min./max. temperature conditions	-5 to 100 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.