

TUNFLUID HT 2200

High-temperature synthetic oil for chain lubrication with OMC2 technology

Benefits

- ✓ Excellent wear protection for reliable chain operation
- ✓ Suitable for a wide variety of applications due to its wide temperature range and high thermal stability
- ✓ Increases energy efficiency and lowers operating temperatures due to special OMC2 additive technology to reduce friction

Properties

- ✓ Reduces friction and wear
- ✓ Very good penetration and adhesive properties
- ✓ Minimal evaporation loss
- ✓ Excellent corrosion protection
- ✓ No resin or bonding effect
- ✓ Silicone-free
- ✓ High flash point
- ✓ Fully synthetic and ageing-resistant

Application area

- ✓ Chain lubrication for clamping and drying frames in the textile industry
- ✓ Drive and transport chains in the chemical industry, in paint systems and in wood and plastic processing
- ✓ Chains in baking and drying ovens
- ✓ In the glass-, ceramic-, enamel- and metal-processing industries
- ✓ Ropes, spindles, gears, cylinders and other drive units
- ✓ Under high loads, for long-term lubrication at high and extremely low temperatures
- ✓ Forklift truck chains

Instructions

Observe the machine manufacturer's specifications. Application via drip oiler, central lubrication systems, oil spray systems or by hand.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNFLUID HT 2200	400 ml	0.275 kg	0.383 kg	11AC14017A0400	12 PCS



Technical Product Data	TUNFLUID HT 2200
Density/conditions	0.871 g/cm ³ / at 20°C
Colour spectrum	Redish Clear
Oil basis	Ester
Kinematic viscosity / condition	4100 mm ² /s / at 40°C
Rating copper corrosion/conditions	1-100 / after 24h at 100°C, nach DIN 51811
Min. flashing point /conditions	> 220°C / nach ISO 2592
Pour point	-10 °C
Min./max. temperature conditions	0 to 220 °C