## **Product Information**



## **TUNAIR TS 46**

Semi-synthetic compressor oil for problem-free long-term operation.

### **Benefits**

- Extended oil change intervals due to the particularly high thermal stability of the base oils used
- High wear protection
- Excellent corrosion protection

### **Properties**

- Extremely efficient
- ✓ Little to no condensate formation

### Application area

✓ For use in screw compressors with oil-injection cooling. Also extremely suitable for use as a long-term gearbox oil.

#### Instructions

Use in accordance with the compressor manufacturer's regulations. The multi-grade characteristics of compressor oils mean they fall into viscosity classes ISO VG 32 to ISO VG 68.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNAIR TS 46	20 l	17.3 kg	18.9 kg	11ACI15007L0200	1 PCS

# **Product Information**



Technical Product Data	TUNAIR TS 46
Density/conditions	0.855 g/cm <sup>3</sup> / at 20°C
Colour spectrum	Yellowish
	Clear
Oil basis	Semisynthetic
Kinematic viscosity / condition	46 mm <sup>2</sup> /s / at 40°C
Rating copper corrosion/conditions	1-100 / after 24h at 100°C, nach DIN 51811
Min. flashing point /conditions	220 / in accordance with ISO 2592
Pour point	-15 °C
Min./max. temperature conditions	-10 to 120 °C