

TUNCUT STF

Evaporating, non-water-miscible cooling lubricant

Benefits

- ✓ In all areas where after the forming process, degreasing before additional surface treatments must be avoided
- ✓ Punching and fine punching
- ✓ Drawing and deep drawing
- ✓ Bending, chamfering and forming

Properties

- ✓ Combination of high-performance additives in solvents that evaporate quickly and are not harmful to health.
- ✓ NSF H1 registered
- ✓ ISO 21469, Kosher- and Halal-certified

Application area

- ✓ Not harmful to health
- ✓ Evaporates with almost no residue
- ✓ Good pressure rating and highly resilient
- ✓ Reduces friction and wear
- ✓ Extends tool life
- ✓ No cleaning needed before additional surface treatments

Instructions

Apply product undiluted. Application via spray system, brush or roller

If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is used as a corrosion-protection film for surfaces in contact with food, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCUT STF	200 l	152 kg	168 kg	11ACL15039L2000	24 PCS

Product Information



Technical Product Data	TUNCUT STF
Density/conditions	0.763 g/cm ³ / at 15°C
Colour spectrum	Light yellow Clear
Oil basis	Synthetic / mineral oil combination
Min. flashing point /conditions	56 °C / nach ISO 2592

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20250106

[TUNAP.com](https://www.tunap.com)