Product Information



TUNCUT B 40

Non-water-miscible drilling, cutting and punching fluid for metal working

Benefits

- ✓ Impressive lubrication performance extends tool service life
- For high surface quality
- ✓ Based on a natural base oil and non-hazardous (GHS)
- Excellent adhesion
- Extremely good lubrication performance

Properties

✓ Transparent, natural oil with high-pressure additives and oxidation and corrosion inhibitors

Application area

- Cutting oil for drilling, thread cutting, sawing and turning
- ✓ Forming oil for bending, crimping, folding, deep drawing, forming and punching

Instructions

TUNCUT B 40 is suitable for circulation lubrication systems as well as for application by spraying, rolling, etc.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCUT B 40	200 l	184 kg	204 kg	11ACL15042L2000	1 PCS

Product Information



Technical Product Data	TUNCUT B 40
Density/conditions	0.9225 g/cm ³ / at 20°C
Colour spectrum	Yellowish
	Clear
Oil basis	Native Oil
Kinematic viscosity / condition	43 mm ² /s / at 40°C
Min. flashing point /conditions	280 / in accordance with ISO 2592
Pour point	-10 °C

PI 20250106