

Professional 163 System Agent

Specially developed active agent concentrate for vehicles running on liquefied petroleum gas (LPG). Minimises valve wear (valve impact) and ensures the fuel's long-term stability in combination with MP 164. Prevents the ageing-related oxidation of petrol.



Properties

- ✓ Prevents the ageing-related oxidation of petrol
- ✓ Prevents deposits in the fuel system due to the keep clean effect
- ✓ Minimises valve wear
- ✓ Corrosion protection for the entire fuel system
- ✓ Prevents the formation of residues in the fuel system

Application area

- ✓ After the conversion to liquefied petroleum gas operation
- ✓ For all maintenance on the system
- ✓ For repairs on the system
- ✓ Also suitable for vehicles running on natural gas (CNG)

Instructions

Add the contents of the can to the fuel tank.
In combination with MP 164, an additional dosage is necessary if the fuel tank has been run empty or, at the latest, after 10,000 km.

Dosing

One can is sufficient for up to 80 litres of petrol. Minimum fill level of 10 litres.

Notice

- ✓ Optimal long-term engine protection is only achieved in combination with MP 164 system agent LPG (gas)

Product Description	Contents	Article Number	Packaging Unit
System Agent	375 ml	11AMP16300375AB	24 PCS
Required accessories		Article Number	Packaging Unit
System Agent, 100 ml		1103667	24 PCS

