

## CARGO logic® 642 Radiator Sealant

Immediately and permanently seals hairline cracks and leaking areas in the coolant circuit. Prevents seal transpiration and coolant loss. Compatible with all standard anti-freezes and coolants.



### Properties

- ✓ Secures the coolant circuit against leaks
- ✓ Permanent sealing of hairline cracks and leaking areas Heating taps and water pumps are functionally secured
- ✓ Prevents seal transpiration and coolant loss
- ✓ Seals without bonding
- ✓ Fully compatible with anti-freezes and coolants
- ✓ Neutral against rubber and plastics, light alloys and non-ferrous metals

### Application area

- ✓ For transpiration-soaked head gaskets
- ✓ For non-tight hose connections
- ✓ For hairline cracks in the radiator, cylinder head or engine block
- ✓ In case of coolant loss

### Instructions

Add to a warm engine. Open the heater valves. Let the engine run for at least 20 minutes until the thermostat opens. Then, switch off the engine, check the coolant level, absence of air and leak tightness again.

### Dosing

Sufficient for up to 40 litres of coolant.

### Notice

- ✓ Add to a warm engine. Open the heater valves.
- ✓ Let the engine run for at least 20 minutes until the thermostat opens. Then, switch off the engine, check the coolant level, absence of air and leak tightness again.

Product Description	Contents	Article Number	Packaging Unit
Radiator Sealant	1 l	11AN36421000AB	12 PCS

