

## TUNTEX 1020 Underbody Protection

Bitumen-free long term underbody coating that can be painted over. Suitable for making repairs as well as for PVC-coated underbodies. The permanently elastic and durable rubber-based protective film prevents corrosion from moisture and road salt.



### Properties

- ✓ Protects from moisture and road salt corrosion
- ✓ Highest level of abrasion resistance
- ✓ Can be painted over
- ✓ High coating thickness
- ✓ High level of resistance to ageing

### Application area

- ✓ Compatible on all factory-fitted surfaces, except wax
- ✓ Underbody
- ✓ Wheel arch
- ✓ Front and rear apron
- ✓ Sills
- ✓ New parts
- ✓ Repair sheet metal

### Instructions

Shake can well before use. Layer thickness per work process approx. 1 mm wet film (= 700 µm dry film). For repainting with „water-based paint systems“ allow to dry for at least 3 hours per 500 µm dry film at 23°C / 55% humidity. For repainting with „solvent-based paint systems“ allow to dry for at least 20 minutes. The drying time depends on the ambient temperature/humidity and layer thickness. Clean the spray gun thoroughly after processing.

### Notice

- ✓ Underbody must be clean, corrosion-proof and dry
- ✓ Do not spray on axle, drive shaft, engine, gear, exhaust and brake system

Product Description	Contents	Article Number	Packaging Unit
Underbody Protection	1 l	1400417	12 PCS
Required accessories		Article Number	Packaging Unit
Underbody Coating Gun, 0		1400408	1 PCS

