Product Information



TUNSEAL

3070 Plastic Repair Adhesive

Two-component reaction adhesive. Can be used in particular for plastic repairs in vehicle manufacturing. Good adhesion on steel and aluminium, hard PVC, GFP, PVC, PU and PS hard foam. Not suitable for PP, PTFE.



Properties

- Creates firm yet flexible connections between very different materials
- Can be painted over excellently
- ✓ Working life approx. 2–3 minutes
- Can be sanded after approx. 10 minutes

Application area

- For repairing plastic parts such as unpainted and painted bumpers, mirror housings, headlight housings, door trims etc.
- ✓ For bonding metals such as steel and iron sheets on non-load-bearing bodywork parts

Instructions

The adhesion surfaces must be dry, clean, dust, oil and grease-free. Sanding of the surface is necessary to increase the adhesive properties. Remove the closure and attach the mixing tube. Use cartridge in the K5 1500 gun and discard the first 2–3 cm of the adhesive bead to guarantee optimal mixing.

Notice

✓ Application times apply in a standard climate at 23°C/50% relative humidity.

Product Description	Contents	Article Number	Packaging Unit
Plastic Repair Adhesive	25 ml	1400421	12 PCS
Poguired accordance		Article Number	Dackaging Unit
Required accessories		Article Number	Packaging Unit
Required accessories 2-Component Manual Gun, 0		Article Number 1400377	Packaging Unit 1 PCS

