

TUNSEAL

2061 Windscreen Adhesive Set

Window adhesive with increased initial strength for quick securing of the window and short drive-away time (30 min. with airbag). High-modulus and non-conductive for optimal bodywork stability and corrosion protection. Refer to the operating instructions! Store in a cool and dry place.



Properties

- ✓ High-modulus (shear modulus approx. 2.5 MPa)
- ✓ Improves bodywork stability
- ✓ Not electrically conductive
- ✓ Prevents contact corrosion between the adhesive and the bodywork
- ✓ Ready to drive with double airbag after 30 minutes (to – 18°C)
- ✓ Light, uncomplicated cold processing thanks to larger „big mouth opening“
- ✓ Increased initial strength prevents the window from sliding after adhesion (high tack effect)

Application area

- ✓ Adhesion of front, rear and side windows into the bodywork of vehicles (passenger vehicles, trucks, driver cabs of tractors, fork-lift trucks, special vehicles).

Instructions

The adhesion surfaces must be dry, clean and free from release agents and grease. Clean glass pane with special glass cleaner 2034 or cleaner 2033. Prime the windows and painted adhesion surfaces with primer stick 2035 (leave to dry for at least 10 minutes). Apply TUNSEAL 2060 on dry primer or on residue material. Install window within 15 minutes. Please observe the current technical data sheet.

Notice

- ✓ Store in a cool and dry place. Do not use cleaners containing alcohol directly before and during adhesion (adhesive will no longer harden).
- ✓ Set comprised of:
 - ✓ 1 cartridge of TUNSEAL 2060 window adhesive (310 ml)
 - ✓ 1 bag of TUNSEAL 2034 special glass cleaner (wet and dry cloth)
 - ✓ 1 universal application nozzle
 - ✓ 1 2-in-1 primer
- ✓ From 24 August 2023, adequate training must be completed prior to industrial or commercial use.

Product Description	Contents	Article Number	Packaging Unit
Windscreen Adhesive Set	310 ml	1400438	12 PCS
Additional accessory		Article Number	Packaging Unit
Special Cleaning Cloth, 10 ml		1400432	1 PCS

