

## TUNSEAL 2062 Windscreen Adhesive Set

Window adhesive (film bag) with high initial strength for a fast windscreen fitting with a short waiting time (30 min with airbag). High-modulus and non-conductive for optimal bodywork stability and corrosion protection. Refer to the operating instructions. Store in a cool and dry place.



### Properties

- ✓ High-modulus (shear modulus approx. 2.5 MPa)
- ✓ Improves bodywork stability
- ✓ Not electrically conductive
- ✓ Prevents contact corrosion between the adhesive and the bodywork
- ✓ Ready to drive with double airbag after 30 minutes (to -18°C)
- ✓ Increased initial strength prevents the window from sliding after adhesion (high tack effect)

### Application area

- ✓ Adhesion of front, rear and side windows into the bodywork of vehicles (passenger vehicles, trucks, driver cabs of tractors, fork-lift trucks, special vehicles).

### Instructions

Refer to the operating instructions. The adhesion surfaces must be dry, clean and free from release agents and/or grease. Clean the glass pane with special glass cleaner 2034. Prime the windows and painted adhesion surfaces with primer stick 2035 (leave to flash off for at least 10 minutes). Apply TUNSEAL 2060 on dry primer or on residue material. Install window within 15 minutes. Please observe the current technical data sheet.

### Notice

- ✓ Store in a cool and dry place. Do not use cleaners containing alcohol directly before and during adhesion (adhesive will no longer harden).
- ✓ Set comprised of:
- ✓ 1 foil sausage pack of TUNSEAL 2060 window adhesive (400 ml)
- ✓ 1 bag of TUNSEAL 2034 special glass cleaner (wet and dry cloth)
- ✓ 1 universal application nozzle
- ✓ 1 2035 2-in-1 primer
- ✓ 1 set of instructions

Product Description	Contents	Article Number	Packaging Unit
Windscreen Adhesive Set	400 ml	1400439	12 PCS

