Product Information

TS330 Tyre Sealant

Full control, even when it gets rough: Our tyre sealant is the ideal companion for tubeless tyres. It reliably seals holes up to 8 mm due to aramid fibres and fills gaps in a flash. The water-based, ammonia-free formula protects the material - ideal for mountain, gravel and racing bikes and also as a preventive measure in tubular tyres.

german cycling
Wir sind Radsport.
TUNAP SPORTS
OFFIZIELLER AUSRÜSTER

Seals holes up to 8 mm.

- ✔ Remains stable in the tyre for 6 to 12 months.
- ✔ Easy to use - no tools required.

Properties

- ✔ Reliably seals: Seals holes up to 8 mm, even in harsh conditions.
- ✔ Keeps going: Remains stable in the tyre for 6 to 12 months.
- ✔ Perfect sealing: Reliably fills gaps between the rim and tyre bead.
- ✔ Easy to use: Apply directly into the valve from the bottle - no tools required.
- ✔ Gentle on materials: Water-based and ammonia-free.
- ✔ Also withstands pressure: Suitable for high tyre pressures - including racing bikes.
- ✔ CO_2 compatible: Also works with CO_2 cartridges.
- ✔

Application area

- ✔ Ideal for racing bike, mountain bike and gravel bike tyres
- ✔ For the fitting of and continuous riding on tubeless systems
- ✔ Puncture protection also for tubular tyres

Instructions

Remove the valve core by unscrewing. Open the upper screw cap and place the opening in the valve. Position the valve at the bottom. Fill carefully with the desired quantity. Place the wheel in the 9 o'clock position and open the bottle. Reinstall the valve core. Turn the wheel to distribute the sealant evenly. Inflate the tyres. If necessary, roll the wheel back and forth to check that it is sealed correctly between the rim and the tyre.

Dosing

Racing bike tyre - 30 to 50 ml
Mountain bike 27.5 inch - 80 to 100 ml
Mountain bike 29 inch - 100 to 140 ml
Gravel bike - 50 to 80 ml

Notice

- ✔ Set the valve to the 6 o'clock position for filling. Before opening the bottle, set the valve and bottle to the 9 o'clock position.

Product Description	Contents	Article Number	Packaging Unit
Tyre Sealant	250 ml	1401293	12 PCS

The information herein is the product of careful testing. It is to be considered a recommendation compliant with state of the art knowledge where use is concerned. We cannot accept any liability whatsoever in view of the multiplicity of possible uses and working methods. No contractual relationship is hence implied and no ancillary obligations arise from any contract of sale that may be made. Product information is only valid in its latest current form. TUNAP (U.K) Limited | Unit L4 Deacon Trading Estate, Morley Road, Tonbridge, Kent TN9 1RA | Telephone +44 (0) 1732 365163 | e-Mail: sales@tunap.co.uk

Product Information

The information herein is the product of careful testing. It is to be considered a recommendation compliant with state of the art knowledge where use is concerned. We cannot accept any liability whatsoever in view of the multiplicity of possible uses and working methods. No contractual relationship is hence implied and no ancillary obligations arise from any contract of sale that may be made. Product information is only valid in its latest current form. TUNAP (U.K) Limited | Unit L4 Deacon Trading Estate, Morley Road, Tonbridge, Kent TN9 1RA | Telephone +44 (0) 1732 365163 | e-Mail: sales@tunap.co.uk